

TR13/TR15 Rubber covered straight valve designed primarily for passenger, light truck, farm implement, and industrial tubes.

TR 13 Length 1.38"

TR 15 Length 1.38"



TR218A/TR220A Two piece air/liquid type valves for rear farm, farm implement and grader applications. The external threads are .482"-26 and supplied with a rim nut.

TR 218A Length 1.63"

TR 220A Length 2.00"

TR 75A/77A/78A/175A/179A Rubber based metal stem valve for light, medium and heavy truck and some industrial applications. This valve is generally bent at 85° and can be used in liquid fill applications.

TR 75A Length 3.35" (Equivalent Valve TR 440)

TR 77A Length 4.53" (Equivalent Valve TR 441)

TR 78A Length 5.51" (Equivalent Valve TR 442)

TR 175A Length 4.92" (Equivalent Valve TR 443)

TR 179A Length 6.10" (Equivalent Valve TR 445)



TR 150 Hand bendable rubber covered valves for light truck and some front farm, farm implement and industrial applications. For use with .618"/.633" diameter rim holes.

TR 150 Length 3.69"

TR87 Rubber based metal stem valve for industrial applications. This valve fits .445"/.461" diameter rim hole and is generally bent at 90°.

TR 87 Length 1.75"



TRJS2 Small rubber based metal stem valve for industrial applications. This valve fits .445"/.461" diameter rim hole and can be used with liquid fill. Valve is bent at 70° and supplied with a washer and nut.

JS-2 Length 2.0"

TRJ1175C Screw-on metal valve to rubber base. Used for severe duty applications specifically for mining. Stem dimensions are 1" height to bend, 5.5" to tip of stem. Diameter of valve is 3.34"

